

```
/**
 * A container for a single item. No copy is made of the contained item, so the
 * client retains an alias to the inserted item.
 *
 * @convention value is null ==> isEmpty
 * @correspondence isEmpty ==> contains is empty <br />
 *                 !isEmpty ==> value in contains
 */
public class PlasticBox<T> implements Box<T> {

    /**
     * The contained item, if one exists. If the PlasticBox is empty, there is no
     * guarantee on value. In particular, it might or might not be null.
     */
    private T value;

    /**
     * True if and only if the PlasticBox is empty. When isEmpty is true, it
     * might not be safe to dereference value, as that field might be null.
     */
    private boolean isEmpty;

    /**
     * Initializes a PlasticBox to be empty.
     *
     * @ensures isEmpty
     */
    public PlasticBox() {
        isEmpty = true;
    }

    public boolean contains(T target) {
        if (!isEmpty) {
            if (target.equals(value)) {
                return true;
            }
        }
        return false;
    }

    public void insert(T item) {
        if (isEmpty) {
            isEmpty = false;
            value = item;
        }
    }

    public T removeAny() {
        assert (!isEmpty);
        isEmpty = true;
        return value;
    }

    public int size() {
        if (isEmpty) {
            return 0;
        }
        return 1;
    }
}
```