

```
// structure/BigBlob.java -- Everything in one file.
// Fred Swartz - December 2004

// A common style of programming is to put all processing
// in the GUI. This works Ok as long as the "model", the
// logic, is so small that it isn't worth putting into
// a separate class.
//
// However, mixing model with presentation usually makes the program hard
// to read, and the inevitable growth of the program leads to a mess.
//
// This fails the simple Interface Independence test.
// Could the model easily work with a command line or web interface? No.
//
// It also fails the Model Independence test.
// Could we easily change the model, eg, to BigDecimal? No.

import java.awt.*;
import javax.swing.*;
import java.awt.event.*;
import java.math.BigInteger;

public class BigBlob {
    public static void main(String[] args) {
        JFrame window = new BigBlobGUI();
        window.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        window.setTitle("Simple Calc");
        window.setVisible(true);
    }
}

class BigBlobGUI extends JFrame {
    //... Constants
    private static final String INITIAL_VALUE = "1";

    //... Components
    private JTextField m_totalTf = new JTextField(10);
    private JTextField m_userInputTf = new JTextField(10);
    private JButton m_multiplyBtn = new JButton("Multiply");
    private JButton m_clearBtn = new JButton("Clear");

    private BigInteger m_total; // The total current value state.

    /** Constructor */
    BigBlobGUI() {
        //... Initialize components and model
        m_total = new BigInteger(INITIAL_VALUE);
        m_totalTf.setText(INITIAL_VALUE);
        m_totalTf.setEditable(false);

        //... Layout the components.
        JPanel content = new JPanel();
        content.setLayout(new FlowLayout());
        content.add(new JLabel("Input"));
        content.add(m_userInputTf);
        content.add(m_multiplyBtn);
        content.add(new JLabel("Total"));
        content.add(m_totalTf);
        content.add(m_clearBtn);

        //... finalize layout
        this.setContentPane(content);
    }
}
```

```
        this.pack();

        //... Listener to do multiplication
        m_multiplyBtn.addActionListener(new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                try {
                    m_total = m_total.multiply(new BigInteger(m_userInputTf.getText()));
;
                    m_totalTf.setText(m_total.toString());
                } catch (NumberFormatException nex) {
                    JOptionPane.showMessageDialog(BigBlobGUI.this, "Bad Number");
                }
            }
        });

        //... Listener to clear.
        m_clearBtn.addActionListener(new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                m_total = new BigInteger(INITIAL_VALUE);
                m_totalTf.setText(INITIAL_VALUE);
            }
        });
    }
}
```